

S14R

1.0AMP. SCHOTTKY BARRIER RECTIFIERS


FEATURE

- . For surface mounted application
- . High current capability
- . Low forward voltage drop
- . Low power loss, high efficiency
- . High surge current capability
- . High temperature soldering guaranteed:
260°C/10 seconds at terminals.

MECHANICAL DATA

- . Terminal: Solder plated
- . Case: Molded with UL-94 Class V-0 recognized
Flame Retardant Epoxy (free halogen)
- . Polarity: color band denotes cathode
- . Packaging: 12mm tape per EIA STD RS-481

SMF



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Type Number	SYM BOL	S14R	units
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	40	V
Maximum RMS Voltage	V_{RMS}	28	V
Maximum DC blocking Voltage	V_{DC}	40	V
Maximum Average Forward Rectified Current at $T_L = 90^\circ\text{C}$	$I_{F(AV)}$	1.0	A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	30.0	A
Maximum Forward Voltage at 1.0A DC	V_F	0.55	V
Maximum DC Reverse Current @ $T_j = 25^\circ\text{C}$ at rated DC blocking voltage @ $T_j = 100^\circ\text{C}$	I_R	0.2	mA
		20.0	
Typical Junction Capacitance (Note1)	C_J	110	pF
Typical Thermal Resistance (Note2)	$R_{(JA)}$	88	$^\circ\text{C/W}$
	$R_{(JC)}$	32	
Storage Temperature	T_{STG}	-55 to +150	$^\circ\text{C}$
Operating Junction Temperature	T_J	-55 to +125	$^\circ\text{C}$

Note:

1. Measured at 1.0 MHz and applied reverse voltage of 4.0Vdc
2. Measured on P.C.Board with 0.2×0.2”(5.0×5.0mm)Copper Pad Areas.

RATING AND CHARACTERISTIC CURVES (S14R)

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.3-MAXIMUN NON-REPETITIVE FORWARD SURGE CURRENT






FIG.4-TYPICAL REVERSE CHARACTERISTICS




Marking and packaging illustration

1、Marking



SYMBOL	Explanation
A	Color Band Denotes Cathode
B	Product Name
C	Date Code

2、Packaging



SPECIFICATIONS mm(inch)		PACKAGE	
SYMBOL		SMF	
ITEM			
Carrier width	A	2.93(0.115)Max	
Carrier length	B	4.85(0.191)Max	
Sprocket hole	d	ø1.55(0.061)Typ	
Reel outer diameter	D	330.0(13.0)Typ	
Reel inner diameter	D1	50.0(1.969)Min	
Feed hole diameter	D2	13.0(0.512)Typ	
Sprocket hole position	J	1.75(0.069)Typ	
Punch hole position	H	5.50(0.217)Typ	
Carrier depth	K	1.42(0.056)Typ	
Punch hole pitch	P	4.00(0.157)Typ	
Sprocket hole pitch	P0	4.00(0.157)Typ	
Embossment center	P1	2.00(0.079)Typ	
Overall tape thickness	T	0.25(0.010)Typ	
Tape width	W	12.0(0.472)Typ	
Reel width	W1	12.4(0.488)Min	