

## Features

- Uses PingWei advanced PerfectMOS2 technology
- Extremely low on-resistance  $R_{DS(on)}$
- Excellent  $Q_g \times R_{DS(on)}$  product(FOM)
- Qualified according to AEC-Q101 criteria

## Benefits

- High robustness and reliability
- Increases maximum current capability
- Low power loss, high power density
- Easy paralleling

## Applications



- General Automotive Applications
- Battery management
- DC-DC



**100% DVDS Tested**  
**100% Avalanche Tested**

## Product Summary

$V_{DS}$	40V
$R_{DS(on)}@10V$ typ	1.36mΩ
$I_D$ (Silicon limit)	199A



## Package Marking and Ordering Information

Part #	Marking	Package	Packing	Reel Size	Tape Width	Qty
PWC016N04ESQ	C016N04ESQ	DFN5*6	Tape&Reel	13 inches	12mm	5000pcs

## Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Drain-source voltage	$V_{DS}$	40	V
Continuous drain current	$I_D$	199	A
$T_C = 25^\circ\text{C}$ (Silicon limit)		120	
$T_C = 25^\circ\text{C}$ (Package limit)		120	
$T_C = 100^\circ\text{C}$ (Silicon limit)		30	
$T_a = 25^\circ\text{C}$ (See RthJA)			
Pulsed drain current ( $T_C = 25^\circ\text{C}$ )	$I_{D \text{ pulse}}$	480	A
Avalanche energy, single pulse (L=0.3mH)	$E_{AS}$	163	mJ
Gate-Source voltage	$V_{GS}$	$\pm 20$	V
Power dissipation	$P_{tot}$	119	W
$T_C = 25^\circ\text{C}$		2.6	
$T_a = 25^\circ\text{C}$ (See RthJA)			
Operating junction and storage temperature	$T_j, T_{stg}$	-55...+175	$^\circ\text{C}$
Reflow soldering temperature (10s)	$T_{sold}$	260	$^\circ\text{C}$

## Thermal Resistance

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Thermal resistance, junction - case.	RthJC	-	-	1.26	°C/W	-
Thermal resistance, junction - ambient(min. footprint)	RthJA	-	-	57	°C/W	1 inch <sup>2</sup> , 2oz single copper FR-4 PCB

## Electrical Characteristic (at T<sub>j</sub> = 25 °C, unless otherwise specified)

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		

## Static Characteristic

Drain-source breakdown voltage	BV <sub>DSS</sub>	40	-	-	V	V <sub>GS</sub> =0V, I <sub>D</sub> =250uA
Gate threshold voltage	V <sub>GS(th)</sub>	2	-	4	V	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250uA
Zero gate voltage drain current	I <sub>DSS</sub>	-	-	1 100	μA	V <sub>DS</sub> =40V, V <sub>GS</sub> =0V T <sub>j</sub> =25°C T <sub>j</sub> =150°C
Gate-source leakage current	I <sub>GSS</sub>	-	-	±100	nA	V <sub>GS</sub> =±20V, V <sub>DS</sub> =0V
Drain-source on-state resistance	R <sub>DS(on)</sub>	-	1.36	1.6	mΩ	V <sub>GS</sub> =10V, I <sub>D</sub> =50A
Transconductance	g <sub>fs</sub>	-	320	-	S	V <sub>DS</sub> =5V, I <sub>D</sub> =50A

## Dynamic Characteristic

Input Capacitance	C <sub>iss</sub>	-	3838	-	pF	V <sub>GS</sub> =0V, V <sub>DS</sub> =20V, f=250KHz
Output Capacitance	C <sub>oss</sub>	-	1277	-		
Reverse Transfer Capacitance	C <sub>rss</sub>	-	38	-		
Gate Total Charge	Q <sub>G</sub>	-	52	-	nC	V <sub>DS</sub> =20V, I <sub>D</sub> =20A, V <sub>GS</sub> =10V
Gate-Source charge	Q <sub>gs</sub>	-	20	-		
Gate-Drain charge	Q <sub>gd</sub>	-	6	-		
Turn-on delay time	t <sub>d(on)</sub>	-	16	-	ns	V <sub>GS</sub> =10V, V <sub>DD</sub> =20V, R <sub>G_ext</sub> =1.6Ω, I <sub>D</sub> =20A
Rise time	t <sub>r</sub>	-	34	-		
Turn-off delay time	t <sub>d(off)</sub>	-	43	-		
Fall time	t <sub>f</sub>	-	22	-		
Gate resistance	R <sub>G</sub>	-	2.1	-	Ω	V <sub>GS</sub> =0V, V <sub>DS</sub> =0V, f=1MHz

## Body Diode Characteristic

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Body Diode Forward Voltage	$V_{SD}$	-	-	1.2	V	$V_{GS}=0V, I_{SD}=50A$
Body Diode Continuous Forward Current	$I_S$	-	-	120	A	TC = 25°C
Body Diode Pulsed Current	$I_S$ pulse	-	-	480	A	TC = 25°C, $t_p = 100\mu s$
Body Diode Reverse Recovery Time	$t_{rr}$	-	71	-	ns	$I_F=50A, V_R=20V$
Body Diode Reverse Recovery Charge	$Q_{rr}$	-	81	-	nC	$dI/dt=100A/\mu s$

## Typical Performance Characteristics

Fig 1: Output Characteristics




Fig 2: Transfer Characteristics




Fig 3:  $R_{DS(on)}$  vs Drain Current and Gate Voltage




Fig 4:  $R_{DS(on)}$  vs Gate Voltage




Fig 5:  $R_{DS(on)}$  vs. Temperature




Fig 6:  $V_{GS(th)}$  vs. Temperature




Fig 7: BVdss vs. Temperature




Fig 8: Capacitance Characteristics




Fig 9: Gate Charge Characteristics




Fig 10: Body-diode Forward Characteristics




Fig 11: Power Dissipation




Fig 12: Drain Current Derating




Fig 13: Safe Operating Area







Fig 14: Max. Transient Thermal Impedance





## Test Circuit & Waveform



Gate Charge Test Circuit & Waveform





Resistive Switching Test Circuit & Waveforms




Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms



## Package Outline: DFN5X6



SYMBOL	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	0.90	1.10	0.035	0.043
b	0.25	0.50	0.010	0.020
c	0.10	0.30	0.004	0.012
D	4.80	5.30	0.189	0.209
D1	4.90	5.50	0.193	0.217
D2	3.92	4.20	0.154	0.165
E	5.65	5.85	0.222	0.230
E1	5.90	6.20	0.232	0.244
E2	3.33	3.78	0.131	0.149
E3	0.80	1.00	0.031	0.039
e	1.27		0.050	
L	0.40	0.70	0.016	0.028
L1	0.65		0.026	
L2	0.00	0.15	0.000	0.006
K	1.00	1.50	0.039	0.059



## Revision History

Revision	Date	Major changes
2.0	2026/6/6	Company Name Change

## Disclaimer

Any and all semiconductor products have certain probability to fail or malfunction, which may result in personal injury, death or property damage. Customer are solely responsible for providing adequate safe measures when design their systems.

The product is not intended for use in applications that require extraordinary levels of quality and reliability, such as aviation/aerospace and life-support devices or systems.

Buyer is responsible for its products and applications using PingWei products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by PingWei.

"Typical" parameters which may be provided in PingWei data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY. FUNCTION OR DESIGN OR OTHERWISE